



Durham Boat Company, Inc.
220 Newmarket Rd.
Durham, NH 03824

BBG Boat Ordering Information:

General Information about the user(s):

Height

Weight

Body proportions (Long torso, short torso, average)

Shoe size

Ankle flexibility

Skill level of rower

Type of water the person will be rowing on (always smooth, some rough, or mostly rough)

Seats

Seats top choices are medium or large.

Medium is recommended for lightweight men and women.

Large for heavyweight men and women in all boat classes.

Track width is: 18.0 cm for all BBG racing singles or 23 cm for 2x/4x and 28 cm for 8+.

High seat supports are standard on all BBG boats with Medium or Low supports available.

Seat Accessories: Durham Foam Seat Pad included in tool kit

Foot Stretchers

Choices of Foot Stretcher type for Olympia, Olympia X, Champion X:

2005 Foot Stretcher: With standard foot plate or New Wave style foot plate (14 cm. 15cm. or 16 cm. shoe spread plates available for all boat classes.

Foot Plate Angle:

Steep – 45 degrees (must have great ankle flexibility)

Average – 42.5 degree (average ankle flexibility) Flat~ 40 degrees (for limited ankle flexibility)

Other: _____

Shoe Type:

DBC: Red/Black, Blue/black or white

NewWave: Red/Blue/Green

Shoe Size:

Men US size/width: _____

Women US size/width: _____

Shoe Placement on the Foot stretcher:

Shoe Height: (Low, medium or high)

Shoe Splay: (Straight up and down, degrees of splay (toes outward))

Riggers

Side mounted tubular are standard on large and medium hull. Top mounted tubular can be purchased as a special order on small hulls.

Rigging Specifications:

Average Spread +/- 6 cm for sculling: _____cm.

(Measured from the centerline on one pin to the center of the other pin)

Average Span +/- 3 cm for sweep: _____cm.

(Measured from the centerline of the boat to the center of the pin)

Average Height +/- 1.5 cm(sculling) or +/- 1 cm (sweep): _____cm.

(Measured from the top of the seat hole to the mid-point of the lock)

Through the pin distance (0 to 10 cm) _____cm.

(Measured from the center of the seat hole to the center of the lock pin)

For sculling only: Do you row left over right? _____.

How much left over right?

Standard = 5 mm

High left over right = 10 mm

Low left over right = Flat or no overlap

Custom left over right = _____mm.

Oar Locks:

For Sculling

MK-1 Magik scull locks (standard on Olympia X singles)

C2 Inset type scull locks

Martinoli insert type scull locks

Martinoli pitch plate scull locks

For Sweep

C2 Inset type sweep locks or Martinoli insert type sweep locks standard

Other Rigger Accessories that are standard:

Carbon Rigger Pitch Meter

Rigger Bag (only available for side mounted tubular riggers)

Thick snap-in height spacers

Fins

All customers receive a spare Al fin

All customers receive either a sailboard style carbon fin or a parallelogram carbon fin.

Indicate which type of carbon fin is desired: _____

Note: 1. The sailboard style fin is best for going straight, stability and in cross winds.

2. The parallelogram fin is best for turning and is best for shedding weeds.

Tool Kit and Accessories

Included: Metric wrenches, an assortment of spare fasteners, pitch inserts, thin and thick spacers, carbon pitch meter, spare Al fin, seat pad, padded rigger bag, BBG T shirt and DBC T shirt.